## CORRECTED VERSION

#### (19) World Intellectual Property Organization International Bureau



# 

#### (43) International Publication Date 31 May 2001 (31.05.2001)

#### **PCT**

### (10) International Publication Number WO 01/39163 A2

(51) International Patent Classification<sup>7</sup>:

G09G

(81) Designated States (national): JP, KR.

PCT/EP00/10963 (21) International Application Number:

(22) International Filing Date:

2 November 2000 (02.11.2000)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 09/447,544 23 November 1999 (23.11.1999) US

(71) Applicant: KONINKLIJKE PHILIPS ELECTRON-ICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventor: LAMBERT, Nicholaas; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: GROENENDAAL, Antonius, W., M.; Internationaal Octrooibureau B.V., Prof Holstlaan 6, NL-5656 AA Eindhoven (NL).

(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

#### Published:

without international search report and to be republished upon receipt of that report

(48) Date of publication of this corrected version:

27 December 2001

(15) Information about Correction: see PCT Gazette No. 52/2001 of 27 December 2001, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



(54) Title: SELF DIAGNOSTIC AND REPAIR IN MATRIX DISPLAY PANEL

(57) Abstract: A matrix display panel having a plurality of columns, comprising a plurality of circuits each being adapted for selectively accessing one of said columns; an interface, communicating data with said plurality of circuits; at least one redundant circuit, adapted for selectively accessing each of said columns and communicating data with said interface; a test circuit, for comparing data communicated by a respective one of said circuits and said redundant circuit; and means for selectively logically replacing a respective circuit with said redundant circuit.